

Inductive Sensors



Housing Style - Rectangular	Part Number	ID Number	Features	Embeddable	Sensing Range (mm)	Output
8.0 mm - Embeddable, Potted-In Cable 	Bi 5-Q08-AD4X/S34	S4414550	<i>Weld-field Immune</i>	•	5	2-Wire DC
	Bi 5U-Q08-AN6X2	S1608911	<i>Uprox</i>	•	5	3-Wire DC NPN
	Bi 5-Q08-AN6X2/S34		<i>Weld-field Immune</i>	•	5	
	Bi 7-Q08-AN6X2	S1601620	<i>Ext. Range</i>	•	7	
	Bi 8U-Q08-AN6X2	S1662007	<i>Uprox</i>	•	8	
	Bi 5U-Q08-AP6X2	S1608901	<i>Uprox</i>	•	5	3-Wire DC PNP
	Bi 5-Q08-AP6X2/S34	S1600800	<i>Weld-field Immune</i>	•	5	
	Bi 7-Q08-AP6X2	S1601600	<i>Ext. Range</i>	•	7	
	Bi 8U-Q08-AP6X2	S1662006	<i>Uprox</i>	•	8	
	Bi 5-Q08-VN6X2	S1600200	<i>Comp. Outputs</i>	•	5	4-Wire DC NPN
	Bi 5-Q08-VN6X2/S34		<i>Weld-field Immune</i>	•	5	
	Bi 7-Q08-VN6X2	S1600920	<i>Ext. Range</i>	•	7	
	Bi 5-Q08-VP6X2	S1600100	<i>Comp. Outputs</i>	•	5	4-Wire DC PNP
	Bi 5-Q08-VP6X2/S34	S1600101	<i>Weld-field Immune</i>	•	5	
	Bi 7-Q08-VP6X2	S1600900	<i>Ext. Range</i>	•	7	
Bi 5-Q08-Y1X	S4054000			•	5	2-Wire NAMUR

For detailed sensor specifications see Section M.
Normally Closed versions available upon request, consult factory.



Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Front Cap/Face	Power LED	Output LED	Mating Cord, Cable Length/Jacket	Wiring Diagram #	Wiring Diagrams
10-65 VDC	50	≤100	-25 to +70	IP 67	Zinc	PA 12	N/A	YE	2M/PVC	1	Diagram 1
	1000	≤200	-30 to +85	IP 67	Zinc	PA 12	GN	YE	2M/PVC	2	Diagram 2
10-30 VDC	300	≤100	-25 to +70	IP 67	Zinc	PA 12	GN	YE	2M/PVC	2	
	500	≤200	-25 to +70	IP 67	Zinc	PA 12	GN	YE	2M/PVC	2	
	1000	≤200	-30 to +85	IP 67	Zinc	PA 12	GN	YE	2M/PVC	2	
10-30 VDC	1000	≤200	-30 to +85	IP 67	Zinc	PA 12	GN	YE	2M/PVC	3	Diagram 3
	300	≤100	-25 to +70	IP 67	Zinc	PA 12	GN	YE	2M/PVC	3	
	500	≤200	-25 to +70	IP 67	Zinc	PA 12	GN	YE	2M/PVC	3	
	1000	≤200	-30 to +85	IP 67	Zinc	PA 12	GN	YE	2M/PVC	3	
10-30 VDC	1000	≤200	-25 to +70	IP 67	Zinc	PA 12	GN	YE	2M/PVC	4	Diagram 4
	300	≤100	-25 to +70	IP 67	Zinc	PA 12	GN	YE	2M/PVC	4	
	500	≤200	-25 to +70	IP 67	Zinc	PA 12	GN	YE	2M/PVC	4	
10-30 VDC	1000	≤200	-25 to +70	IP 67	Zinc	PA 12	GN	YE	2M/PVC	5	Diagram 5
	300	≤100	-25 to +70	IP 67	Zinc	PA 12	GN	YE	2M/PVC	5	
	500	≤200	-25 to +70	IP 67	Zinc	PA 12	GN	YE	2M/PVC	5	
5-30 VDC	1000	Remote	-25 to +70	IP 67	Zinc	PA 12	N/A	YE	2M/PVC	6	Diagram 6

Rectangular

For material descriptions see page M22.